



SAMPLA BELTING NORTH AMERICA LLC

40 Centre Drive, Orchard Park, NY 14127, USA

Phone : +1.716.667 7450 or 1.888.755 7450 (toll free from US only)

Fax : +1.716.667 7428 or 1.888.324 7428 (toll free from US only)

E-mail: info@sampla.us Internet: www.sampla.us

RAW B series - mm

CARRYING COVER						GENERAL										
CODE	Type	Thickness	Hardness	Colour	Possible structures	Nº of plies	Weft	Max. production width	Antistatic	Total thickness	Mass	Pull per 1%	Work temperature range	Minimal roller diameters Flexion	Minimal roller diameters Counterfl	FDA Approval
-	-	mm	°ShA	-	-	-	-	mm	-	mm	kg/ m²	daN/ cm	°C	-	-	-
0	B21	0.1	-	GREEN	-	2	F	3000	NO	2	2.3	16	-10+100	30	30	NO
0	B31	0.1	-	GREEN	-	3	F	3000	NO	3.5	4	20	-10+90	80	80	NO

RAW B series - inch

CARRYING COVER						GENERAL										
CODE	Type	Thickness	Hardness	Colour	Possible structures	Nº of plies	Weft	Max. production width	Antistatic	Total thickness	Mass	Pull per 1%	Work temperature range	Minimal roller diameters Flexion	Minimal roller diameters Counterfl	FDA Approval
-	-	in	°ShA	-	-	-	-	in	-	in	lb/ ft²	lbf/ in	° F	-	-	-
0	B21	0.004	-	GREEN	-	2	F	118	NO	0.079	0.47	91.4	14 +212	1.2	1.2	NO
0	B31	0.004	-	GREEN	-	3	F	118	NO	0.138	0.82	114.2	14 +212	3.1	3.1	NO



SAMPLA BELTING NORTH AMERICA LLC

40 Centre Drive, Orchard Park, NY 14127, USA

Phone : +1.716.667 7450 or 1.888.755 7450 (toll free from US only)

Fax : +1.716.667 7428 or 1.888.324 7428 (toll free from US only)

E-mail: info@sampla.us Internet: www.sampla.us

RAW R series - mm

CARRYING COVER						GENERAL										
CODE	Type	Thickness	Hardness	Colour	Possible structures	Nº of plies	Weft	Max. production width	Antistatic	Total thickness	Mass	Pull per 1%	Work temperature range	Minimal roller diameters Flexion	Minimal roller diameters Counterfl	FDA Approval
-	-	mm	°ShA	-	-	-	-	mm	-	mm	kg/ m ²	daN/ cm	°C	-	-	-
0	R10	-	-	WHITE	-	2	R	3000	YES	1.2	1.3	8	-10+90	30	30	YES
0	R11	-	-	WHITE	-	2	F	3000	NO	1.4	1.4	6	-10+90	15	15	YES
0	R12	-	-	WHITE	-	2	R	3000	YES	1.1	1.2	8	-30+80	30	30	YES
0	R13	-	-	RAW	-	2	R	2000	YES	1	1.1	6	-10+90	10	10	YES
0	R14	-	-	RAW	-	2	R	2150	NO	1.4	1.5	8	-30+80	30	30	YES
0	R19	-	-	WHITE	-	2	RF	2000	NO	2.4	2.2	10	-10+90	50	50	YES



SAMPLA BELTING NORTH AMERICA LLC

40 Centre Drive, Orchard Park, NY 14127, USA

Phone : +1.716.667 7450 or 1.888.755 7450 (toll free from US only)

Fax : +1.716.667 7428 or 1.888.324 7428 (toll free from US only)

E-mail: info@sampla.us Internet: www.sampla.us

RAW R series - inch

CARRYING COVER						GENERAL										
CODE	Type	Thickness	Hardness	Colour	Possible structures	N ^o of plies	Weft	Max. production width	Antistatic	Total thickness	Mass	Pull per 1%	Work temperature range	Minimal roller diameters Flexion	Minimal roller diameters Counterfl	FDA Approval
-	-	in	°ShA	-	-	-	-	in	-	in	lb/ ft ²	lbf/ in	° F	-	-	-
0	R10	-	-	WHITE	-	2	R	118	YES	0.047	0.27	45.7	14 +194	1.2	1.2	YES
0	R11	-	-	WHITE	-	2	F	118	NO	0.055	0.29	34.3	14 +194	0.6	0.6	YES
0	R12	-	-	WHITE	-	2	R	118	YES	0.043	0.25	45.7	-22 +176	1.2	1.2	YES
0	R13	-	-	RAW	-	2	R	79	YES	0.039	0.23	34.3	14 +194	0.4	0.8	YES
0	R14	-	-	RAW	-	2	R	85	NO	0.055	0.31	45.7	-22 +176	1.2	1.2	YES
0	R19	-	-	WHITE	-	2	RF	79	NO	0.094	0.45	57.1	14 +194	2	2	YES